

## Description

Fire Protection Products' Sight Glass are cast from high quality brass\* alloy. This assures lasting performance and serviceability. Available in both "full flow" and "restricted orifice" design. Flow can be viewed through two high impact Lexan (polycarbonate) windows on either side of the sight glass. All models feature male by female thread patterns for easy "in line" installation. The "full flow" design is suitable for system flow verification. The restricted orifice types can be used to simulate system sprinkler head flow which can be viewed through either window. Not designed to be used under pressure.



## Installation

Installation can be made using readily available field tools and materials. Apply a suitable pipe thread sealant to the either the male or female threads. The brass sight glass with the restricted orifice must be installed so the direction of flow is from the female thread to the male thread. This allows the restricted stream to be viewed through the Lexan (polycarbonate) windows. The unrestricted models may be installed in either direction, however, they should be installed consistent with industry standards. The sight glass threads have been machined according to standard iron pipe thread specifications. Installation is similar to other threaded fittings. **Caution: Do not over tighten. Over tightening will cause the sight glass fitting to crack.**

## Approximate Sight Glass Dimensions

		TAKE OUT	WIDTH	DEPTH
08-529-00	Sight Glass, 1" MxF	3.93"	2.45"	2.68"
08-530-00	Sight Glass, 1" FxF, 1/2" Orifice	3.93"	2.45"	2.68"
08-530-00	Sight Glass, 1 1/4" MxF	3.86"	2.38"	2.71"
08-532-00	Sight Glass, 1" FxF, 1 1/32" Orf	3.93"	2.45"	2.68"
08-533-00	Sight Glass, 1 1/2" FxF	3.26"	2.26"	3.13"
08-535-00	Sight Glass, 2" FxF	3.397"	2.85"	3.7"

## Specifications

### Type:

Cast Sight Glass

### Material:

Body: Brass\* Alloy

Windows: Polycarbonate

### Finish:

Rough Brass\*

### Sizes and Configurations:

08-529-00 1" IPS, MxF

08-530-00 1" IPS, 1/2" Orifice, FxF

08-531-00 1 1/4" IPS, MxF

08-532-00 1" IPS, 1 1/32" Orifice, FxF

08-533-00 1 1/2" IPS, FxF

08-535-00 2" IPS, FxF

\*Contains lead. Not for use in water systems intended for human consumption.



3198 LIONSHEAD AVE  
CARLSBAD, CA 92010  
+ 1 (760) 599-1168  
+ 1 (800) 344-1822  
+ 1 (800) 344-3775 FAX

© 2016 Fire Protection Products, Inc.

The information contained herein is produced in good faith and is believed to be reliable but is provided for guidance and information purposes only. FPPI and its agents cannot assume liability or responsibility for results obtained in the use or misuse of its product by persons whose methods and qualifications are outside and beyond our control. It is the user's responsibility to determine the suitability of, methods of use, preparation prior to use, and appropriate installation for all products purchased from FPPI. It is the user's sole responsibility to observe and adapt such precautions as may be advisable or necessary for the protection of personnel and property in the handling and use of any of our products.